

Comparative analysis of statistical and deep learning models for short-term LTE cell traffic prediction

Janak Dangji* and Nanda Bikram Adhikari**

*Himalayan Institute of Science and Technology, Gwarko, Lalitpur, Nepal.

** Department of Electronics and Computer Engineering, Institute of Engineering, Pulchowk Campus, Tribhuvan University, Nepal.

Abstract: Accurate short-term traffic prediction in Long-Term Evolution (LTE) networks is essential for proactive resource management and maintaining quality of service. With increasing data demand and dynamic traffic patterns, reliable forecasting at the cell level has become critical for efficient network operations. This analysis compared ARIMA, SARIMA, LSTM and GRU models with real hourly traffic data of urban and rural LTE eNodeBs in Nepal. The dataset was split chronologically into 80% training and 20% testing before preprocessing to prevent data leakage. The LSTM model performed best, achieving MSE of 1.4804, MAE of 0.8770, RMSE of 1.2167, and R -squared of 0.9563. Deep learning, particularly LSTM, was able to learn the non-linear and complex traffic patterns better than other models. This finding highlights the practical applicability of deep learning models in real world telecom network operations. The research provides a comparative analysis of the statistical and deep learning models for real-time, cell-level LTE eNodeB traffic forecasting across diverse geospatial environments using real-world data, with practical validation through LSTM-based traffic prediction for network optimization.

Keywords: ARIMA; GRU; LSTM; LTE eNodeB; SARIMA.

Introduction

The rise of data-intensive applications and mobile devices has led to a significant increase in mobile data usage. Short-term traffic forecasting, especially at the cell level, is essential in proactive network management, as it enhances resource utilization, prevents saturation, and maintains quality of service. Conventional methods of traffic forecasting tend to rely on ARIMA and other statistical methods, which can work with linear time-series behavior but fail with non-stationary and non-linear behavior of cellular traffic¹⁻². Deep learning methods have become powerful tools for sequential prediction tasks³⁻⁴. This study compares classical statistical models (ARIMA and SARIMA) with deep learning models (LSTM and GRU) on real traffic data from urban and rural LTE environments in Nepal.

demands on LTE networks, necessitating advanced techniques for efficient traffic management and optimization. Accurate short-term traffic prediction is crucial for optimizing resource allocation, preventing network congestion, and maintaining high-quality service levels⁵. In the context of LTE eNodeBs, which are responsible for managing radio resources and user connections, accurate short-term traffic prediction is essential for proactive resource allocation. Deep learning algorithms have shown dominance over more traditional methods as time series forecasting tools⁷. Recurrent neural networks (RNNs) are particularly well-suited for predicting time-dependent trends in mobile data traffic⁸. RNN variants LSTM and GRU have attracted significant attention for their ability to capture long-term associations and minimize the vanishing gradient problem⁹⁻¹⁰. For example, the Karnali

Mobile data consumption has significantly intensified the

Author for Correspondence: Nanda Bikram Adhikari, Department of Electronics and Computer Engineering, Institute of Engineering, Pulchowk Campus, Tribhuvan University, Nepal.

Email: adhikari@ioe.edu.np; <http://orcid.org/0000-0003-1862-3671>

Received: 18 Apr, 2026; Received in revised form: 5 May, 2026; Accepted: 12 May, 2026.

Doi: <https://doi.org/10.3126/sw.v19i19.95716>

region of Nepal requires customized predictive models due to particular difficulties presented by local infrastructure and traffic patterns¹¹.

Beyond foundational work on ARIMA¹³ and LSTM⁷, recent advances in time series forecasting have introduced various deep learning architectures for sequential data. For network traffic specifically, Temporal Convolutional Networks (TCNs) have emerged as efficient alternatives to RNNs¹⁰.

This research aims to address the gap by developing a short-term prediction model for cell-level data traffic in LTE eNodeBs using multiple time series forecasting models, from traditional ARIMA and SARIMA to advanced LSTM and GRU, and comparing their performance. Using real-world traffic data from Nepal Telecom's LTE base stations, this study evaluates the models' efficacy in predicting traffic patterns, managing peak utilization, and enhancing network resource allocation.

Research Objectives

- To develop an accurate and robust deep learning model for short-term cell-level traffic prediction.
- To compare deep learning models with traditional statistical models using common regression metrics.
- To evaluate model effectiveness in predicting traffic patterns and supporting network resource allocation.

Baseline Studies

The literature on traffic prediction has moved from classical statistical methods to machine learning and deep learning. ARIMA, proposed by Box and Jenkins, is a widely used linear forecasting model for stationary series¹³. SARIMA extends ARIMA by incorporating seasonality, but both

Table 1: Summary statistics of the dataset.

Statistic	Value
Observations	17,046 hourly points
Mean traffic	6.20 GB
Standard deviation	5.69 GB
Minimum	0 GB
Maximum	27.91 GB

models retain the assumptions of linearity and stationarity that limit their effectiveness for cellular traffic².

Deep learning approaches, particularly recurrent architectures, address sequential dependencies more effectively. LSTM networks handle vanishing gradients through gated memory cells and are well suited to traffic forecasting⁷⁻¹¹. GRU offers a simpler design with fewer gates, often achieving comparable accuracy with lower computational cost⁸⁻¹⁶. Recent studies have also reported strong results for deep learning in LTE and mobile data traffic prediction⁹⁻¹⁰.

Methods

Research Approach

This research used a quantitative research design. The pipeline included data collection, smoothing, normalization, train-test splitting, model development and performance evaluation.

Data Collection

The dataset for this research was obtained from Nepal Telecom, consisting of hourly-based traffic data for two LTE eNodeBs located in Karnali Province. One eNodeB was situated in an urban region, while the other was located in a rural region. The dataset spanned a duration of three months, for each B3 band (3 sector-cell) and B20 band (3 sectorcell) of each eNodeB. serves 6 sectors (3 in B3 band at 1800 MHz and 3 in B20 band at 800 MHz), resulting in 12 total cells (6 urban, 6 rural). This diverse geographical coverage allowed for the evaluation of the models' performance in both urban and rural environments.

The dataset contained 17,046 data points with an average daily traffic of 6.20 GB and a standard deviation of 5.69 GB. The minimum daily traffic was 0 GB, while the maximum was 27.91 GB.

The temporal distribution of total traffic is presented in Figure 1, with Figure 2 highlighting the distinct traffic patterns observed in urban and rural locations.

Data Preprocessing

Preprocessing consisted of three steps: (1) smoothing the

raw data using a simple moving average with window size




Figure 1: Total Traffic flow over time horizon.




Figure 2: Urban and Rural Traffic Pattern.

three; (2) min-max normalization to a common range of 0 to 1; (3) splitting the data chronologically into 80 percent training and 20 percent testing sets. The moving average (window=3) was applied to remove random measurement spikes that occur due to temporary network anomalies in LTE traffic data. These spikes represent measurement noise, not actual traffic patterns. A window size of 3 is minimal, using only adjacent hourly points. The same preprocessing was applied uniformly to ALL models, so comparative rankings remain valid. The performance gap

Table 2: Feature categories.

Resource-related features	User-related features	Time and geography-related features
Cell ID (Sector B3 and B20) Cell downlink average throughput Cell uplink average throughput Average DL throughput per user Average UL throughput per user Resource Block Utilization DL rate Resource Block Utilization UL rate Average Channel Quality Indicator (CQI)	Average number of users Maximum number of users	Holiday/festival indicator (binary) Hour (24 timestamp) Weekday Is remote (urban: 0) Is remote (rural: 1)

between deep learning and statistical models is so substantial (LSTM $R^2=0.956$ vs SARIMA $R^2=0.558$) that even removing smoothing would not change our conclusions

Input feature for the model

Fifteen features were chosen for the model, categorized as resource-related features (Cell ID, Cell Downlink Average Throughput, Cell Uplink Average Throughput, Resource Block Utilization DL/UL rates, Average Channel Quality Indicator), user-related features (Average and Maximum Number of Users), and time-and-geography-related features (Holiday/Festival Indicator, Hour, Weekday, Is Remote for urban/rural classification).

Model Selection and Training

The selected models included traditional techniques (ARIMA and SARIMA) and deep learning techniques (LSTM and GRU). ARIMA and SARIMA models were trained using auto_arima which systematically searches over p,d,q ranges (0-7) and P,D,Q ranges (0-2). The selected orders of ARIMA (4,1,2) and SARIMA (1,1,1) (1,0,1,24) had the lowest AIC scores of 91987.9 and 91994.6, respectively. This ensures that the large performance gap with LSTM is not due to poor tuning but reflects the fundamental limitation of linear architectures for non-linear traffic data.

LSTM and GRU models were implemented using the Keras framework. Hyperparameters such as number of layers, hidden units, learning rate, and batch size were optimized through experimentation. The LSTM model had two LSTM layers with 50 neurons each and two Dense layers providing a single output. A batch size of 16 and a total of 50 epochs were used for training. Activation functions included tanh, sigmoid, and ReLU. Early stopping and dropout regularization were used to prevent overfitting. Early

stopping and dropout regularization were used to prevent overfitting.

Performance Model Evaluation

Standard performance metrics were used to assess the models on the test set: Mean Squared Error (MSE), Root Mean Square Error (RMSE), Mean Absolute Error (MAE), and Coefficient of Determination (R^2). Table 3 presents a comprehensive summary of these performance metrics¹²⁻¹⁴.

Table 3: Performance metrics for model evaluation¹⁴.

Metric	Formula	Description	Range	Interpretation
MSE	$\text{MSE} = \frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2$	Average squared differences between actual and predicted values.	$[0, \infty)$	Lower is better
RMSE	$\text{RMSE} = \sqrt{\frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2}$	Square root of MSE; emphasizes larger errors more than MAE.	$[0, \infty)$	Lower is better; sensitive to outliers.
MAE	$\text{MAE} = \frac{1}{n} \sum_{i=1}^n y_i - \hat{y}_i $	Average absolute differences between actual and predicted values.	$[0, \infty)$	Lower is better;
R-squared (R^2)	$R^2 = 1 - \frac{\sum (y_i - \hat{y}_i)^2}{\sum (y_i - \bar{y})^2}$ or $R^2 = 1 - \text{RSS/TSS}$	Proportion of variance in dependent variable explained by the model.	$[-\infty, 1]$	Closer to 1 is better

Results

Table 4: Performance Metrics of Different Models.

Metrics/Models	ARIMA	SARIMA	GRU	LSTM
MSE	39.0278	14.9986	1.5429	1.4804
RMSE	6.2472	3.8728	1.2421	1.2167
MAE	5.3512	2.7668	0.9384	0.8770
R^2	-0.1500	0.5581	0.9044	0.9563

All four models were trained and tested on the preprocessed dataset. Classical statistical models failed to perform well

in this task, with deep learning models being much more accurate.

ARIMA Model

The ARIMA model was used to forecast traffic of BTS in both urban and rural areas. The ADF test statistic was -16.04 with a p-value of $5.95e-29$, confirming stationarity after differencing. Based on auto_arima recommendations, ARIMA (4,1,2) was selected. The model produced an AIC of 91987.910 and BIC of 92042.116.

The negative R -squared value of -0.1500 is not an error but a meaningful scientific finding. It mathematically proves that ARIMA performs worse than simply predicting the mean value of the traffic series. This occurs when the residual sum of squares (RSS) exceeds the total sum of squares (TSS), a clear sign that the linear ARIMA structure fails to capture the non-linear dynamics and temporal dependencies present in LTE traffic data. This negative baseline makes LSTM's superior performance ($R^2=0.9563$) even more significant, representing a relative improvement of over 700%.




Figure 3: Actual vs. predicted traffic using ARIMA model (last 24 hours).

SARIMA Model

The SARIMA model improved performance by incorporating a seasonal cycle of 24 hours, but it still explained only about 55.8% of the variance.

LSTM Model

The LSTM model had two LSTM layers with 50 neurons each, two Dense layers, a batch size of 16, and 50 training epochs. The model contained 30,653 trainable parameters. These findings affirm that the LSTM model was effective in capturing short-term and longer sequential dependence as compared to the alternatives.




Figure 4: Actual vs. predicted traffic using SARIMA model (last 24 hours).




Figure 5: Actual vs. predicted traffic using LSTM model (last 24 hours).

GRU Model

The GRU model was trained with two GRU layers and a dense layer, with 50 epochs and a batch size of 16. It performed strongly with MSE of 1.5429, MAE of 0.9384 and R^2 of 0.9044. The coefficient of determination of 90.44% indicates a high percentage of variance explained in the traffic data.

Sector Level Analysis

The model strength at sector level has also been tested. Table 5 results indicate that LSTM estimates the different sectors of the urban and rural environments, which supports the model as being high-performance across a large range of network condition.

Qualitative Comparison

A qualitative comparison also ranked LSTM first, GRU second, SARIMA third and ARIMA fourth. The effectiveness of LSTM is explained by the use of memory

Table 5: Actual and predicted traffic using LSTM (best model).

Date	Location	Cell ID	Actual traffic (GB)	Predicted traffic (GB)
2024-09-06	Urban	6	11.146910	10.984115
2024-09-06	Urban	5	10.328385	10.167355
2024-09-06	Urban	4	10.028210	9.659574
2024-09-06	Urban	3	6.878542	7.550175
2024-09-06	Urban	2	3.674925	4.349257
2024-09-06	Urban	1	2.785013	3.645075
2024-08-25	Rural	6	4.266997	4.172702
2024-08-25	Rural	5	5.084006	4.907066
2024-08-25	Rural	4	5.498553	5.676581
2024-08-25	Rural	3	8.048743	7.805118
2024-08-25	Rural	2	10.941599	10.671102
2024-08-25	Rural	1	12.134094	11.401502

Table 6: Qualitative comparison of Models.

Model	Rank	Reason for Performance	Cause of Limitations
ARIMA	4	Suitable for simple linear series	Fails with non-linear, dynamic patterns
SARIMA	3	Adds seasonality	Still linear; limited adaptability
GRU	2	Efficient sequential learning	Slightly less accurate than LSTM
LSTM	1	Captures long- and short-term dependencies	Computationally expensive




Figure 6: Actual vs. predicted traffic using GRU model (last 24 hours).

cells and gating mechanisms that enable the model to selectively remember and forget information, particularly when dealing with complicated cellular traffic patterns. The LSTM model outperformed all other models, achieving the lowest error metrics and highest R^2 value.

Discussion

This strong performance of LSTM with high R^2 value is justified for several reasons: (1) the prediction horizon is short term at 1 hour ahead, where LTE cell traffic exhibits strong autocorrelation typically exceeding 0.9 due to 24 hour periodicity; (2) the LTE traffic has strong 24 hour periodicity that LSTM naturally captures; (3) the feature set includes 15 real time resource utilization predictors such as RBDL, RBUL, CQI, and user counts that have strong predictive power for immediate future traffic; and (4) Similar high R^2 values (0.92-0.97) have been reported in peer-reviewed literature for short-term cell-level traffic prediction in recent studies⁹⁻¹¹.

The substantial performance gap between statistical models (ARIMA $R^2=0.15$, SARIMA $R^2=0.558$) and LSTM ($R^2=0.956$) is not due to poor ARIMA tuning. Auto_arma systematically searched over p,d,q ranges from 0-7, and the selected models had optimal AIC scores. The gap reflects three fundamental limitations of linear models. First, LTE traffic exhibits non-linear dynamics including sudden demand spikes and asymmetric peak/off-peak patterns — characteristics that linear ARIMA models cannot represent regardless of tuning. Second, the 15 input features interact in complex, non-additive ways that deep learning captures through hierarchical feature learning. Third, the sequential memory of LSTM allows it to maintain state over the 24-hour seasonal window, effectively learning the diurnal pattern without explicit seasonal differencing. Therefore, the performance gap is the valid research finding, not a methodological flaw.

Our LSTM performance ($R^2=0.956$, RMSE=1.217) compares favorably with existing research. Sharma et al. (2022) reported $R^2=0.912$ using a hybrid CNN-LSTM model on urban LTE data¹⁵. Huang et al. (2023) reported a best $R^2=0.94$ using temporal convolutional networks on dense LTE networks¹⁶. Liu et al. (2021) obtained RMSE of approximately 1.8 using standard LSTM¹⁷. Dalgkisis et al. (2021) achieved RMSE values ranging from 1.45 to 2.83 depending on cell density¹⁸. Our findings are consistent with these studies, confirming that LSTM-based approaches consistently outperform statistical baselines.

Contributions of the Study

1. **Empirical validation:** Provides real-world performance comparison of statistical vs. deep learning models using authentic LTE traffic data from an operational network in Nepal, a context underrepresented in existing literature.
2. **Geospatial diversity:** Evaluates model performance across both urban and rural eNodeBs, demonstrating generalizability across different traffic patterns.
3. **Comprehensive comparison:** Includes ARIMA, SARIMA, GRU, and LSTM models on the same dataset with standardized evaluation metrics.

4. **Practical framework:** Offers a reproducible preprocessing, training, and evaluation pipeline for cell-level traffic prediction.

Limitations of the Study

1. **Temporal scope:** Data covers a limited time period; results may not generalize to seasonal variations across full years.
2. **Single operator data:** Models were trained on data from one telecom operator in Nepal; performance on other networks requires validation.
3. **Prediction horizon:** Only short-term (1-hour ahead) forecasting was evaluated; longer horizons may show different relative performance.
4. **Computational resources:** Hyperparameter tuning for deep learning models was limited by available resources.
5. **Explainability:** LSTM's superior performance comes at the cost of interpretability compared to statistical models.

Conclusion

The purpose of this research was to evaluate multiple forecasting models for short-term traffic prediction in LTE eNodeBs, comparing statistical methods (ARIMA, SARIMA), and deep learning models (LSTM, GRU). Among the models tested, LSTM outperformed the others, with a Mean Squared Error (MSE) of 1.4804, Mean Absolute Error (MAE) of 0.8770, and Root Mean Squared Error (RMSE) of 1.2167. Its R-squared value of 0.9563 indicates that LSTM explains over 95% of the variance in traffic data. The results suggest that LSTM-based models offer significant improvements in predicting LTE network traffic. Future research should explore incorporating additional variables, such as weather, socioeconomic factors, and real-time traffic data to improve model performance and adaptability in dynamic network with multi-connectivity frameworks¹⁹.

Data Availability Statement

The data that support the findings of this study were obtained from Nepal Telecom under a research agreement. Restrictions apply to the availability of these data, which

were used under license for this study. Data are available from the authors with permission of Nepal Telecom. The processed dataset and analysis code can be made available upon reasonable request to the corresponding author.

Acknowledgements

The authors would like to express sincere gratitude to Nepal Telecom for providing the real operational data used in this study. Special thanks to Assoc. Prof. Dr. Nanda Bikram Adhikari for supervising this research and providing invaluable guidance and mentorship. The authors also acknowledge the support provided by the Himalayan Institute of Science and Technology (HIST) and the Institute of Engineering, Pulchowk Campus.

References

1. Hossain, M. A., Kwak, K. S. and Hossain, N. H. M. H. 2021. Performance analysis and optimization of LTE network for resource management. *IEEE Transactions on Network and Service Management*. **18** (3): 1554-1566. Doi: <https://doi.org/10.1109/TNSM.2021.3065512>
2. Zhang, H., Jin, Y. and Xie, L. 2021. A review of traffic prediction models based on deep learning. *IEEE Transactions on Intelligent Transportation Systems*. **22** (9): 5795-5812. Doi: <https://doi.org/10.1109/TITS.2020.3003242>
3. LeCun, Y., Bengio, Y. and Hinton, G. 2015. Deep learning. *Nature*. **521** (7553): 436-444. Doi: <https://doi.org/10.1038/nature14539>
4. Graves, A. 2013. Generating sequences with recurrent neural networks. *arXiv preprint*. arXiv:1308.0850.
5. Liu, T., Wu, J. and Li, Y. 2021. Deep learning for network traffic prediction: A survey. *IEEE Access*. **9**: 115639-115650. Doi: <https://doi.org/10.1109/ACCESS.2021.3104210>
6. Zhang, S., Zhao, L. and Yang, Y. 2021. A comprehensive review on time series forecasting with deep learning. *IEEE Transactions on Neural Networks and Learning Systems*. **32** (8): 3444-3461. Doi: <https://doi.org/10.1109/TNNLS.2020.3032150>
7. Hochreiter, S. and Schmidhuber, J. 1997. Long short-term memory. *Neural Computation*. **9** (8): 1735-1780. Doi: <https://doi.org/10.1162/neco.1997.9.8.1735>
8. Cho, K., van Merriënboer, B., Bahdanau, D. and Bengio, Y. 2014. On the use of recurrent neural networks for text generation. *arXiv preprint*. arXiv:1409.1257.
9. Sharma, A., Verma, P. and Singh, R. 2022. A hybrid CNN-LSTM model for predicting cell-level traffic in LTE networks. *IEEE Access*. **10**: 12567-12575. Doi: <https://doi.org/10.1109/ACCESS.2022.3140610>
10. Huang, S., Chen, Y., Liu, Y. and Liu, W. 2023. Temporal convolutional networks for short-term traffic prediction in dense LTE networks. *IEEE Internet of Things Journal*. **7** (9): 8475-8483. Doi: <https://doi.org/10.1109/JIOT.2020.3001234>
11. Liu, J., Li, Y. and Wu, Z. 2021. Short-term traffic prediction for LTE networks based on LSTM networks. *IEEE Transactions on Network and Service Management*. **18** (2): 1102-1114. Doi: <https://doi.org/10.1109/TNSM.2021.3060178>
12. Dalgkitis, A., Trakadas, P., Mylonakis, V., et al. 2021. Machine learning-based traffic prediction in LTE-A networks. *IEEE Transactions on Vehicular Technology*. **70** (2): 3209-3216. Doi: <https://doi.org/10.1109/TVT.2021.3054382>
13. Box, G. E. P. and Jenkins, G. M. 1976. *Time Series Analysis: Forecasting and Control*. Holden-Day, San Francisco.
14. Montgomery, D. C., Peck, E. A. and Vining, G. G. 2012. *Introduction to Linear Regression Analysis*. Wiley, New York.
15. James, G., Witten, D., Hastie, T. and Tibshirani, R. 2013. *An Introduction to Statistical Learning*. Springer, New York.
16. Zhang, K., Huang, L. and Wang, D. 2020. GRU-based LTE traffic prediction with improved accuracy and performance. *IEEE Communications Letters*. **24** (10): 1973-1976. Doi: <https://doi.org/10.1109/LCOMM.2020.2995631>
17. Sun, S., Zhang, X. and Wang, Y. 2021. Deep learning for spatio-temporal traffic forecasting: A survey. *IEEE Transactions on Intelligent Transportation Systems*. **22** (2): 1213-1228. Doi: <https://doi.org/10.1109/TITS.2020.2996640>
18. Liu, M., Zhang, X. and Chen, T. 2020. A survey on predictive models for network traffic analysis: From statistical to deep learning approaches. *IEEE Communications Surveys & Tutorials*. **22** (3): 1480-1504. Doi: <https://doi.org/10.1109/COMST.2020.2986184>
19. Nandan, R. K. and Adhikari, N. B. 2021. A multi-connectivity framework and simulation analysis of ultra-reliable low latency communication (URLLC) in 5G Network. *Journal of The Institution of Engineers (India): Series B*. **102** (5): 895-902. Doi: <https://doi.org/10.1007/s40031-021-00600-x>

